

## AFTERCOOLERS

Aftercoolers are designed for use in any application where compressed, but cool air is required. With an aftercooler, you can reduce the temperature of hot compressed air for a safer, more usable temperature. Painting, sandblasting and similar projects may require you to use air that is cooler and cleaner than a typical air compressor. Our units are available for use in manufacturing, refining, chemical, pipeline and industrial applications, as well as many other industries.



### FEATURES

- Skid mounted units for easy mobility
- Air-driven units require no electrical power to operate
- Cools processed air to within 10 to 15°F of ambient
- High efficiency filters available for ultra pure air streams
- Dryer combo units or stand alone units available



**MUSTANG SERVICES**  
Rental Air Treatment Equipment



1-800-200-4775



10865 Strang Road  
La Porte, TX 77571



info@rentalairdryers.com



www.rentalairdryers.com



# MUSTANG SERVICES

## Rental Air Treatment Equipment

### AIR DRYERS

Desiccant Dryers or Dryer/Aftercooler combo units are used to provide air that is drier than ordinary compressed air produced by an air compressor. Applications include pipeline drying, electronics manufacturing, food or drug production and refinery applications. Dryers are rated for NEMA 4 outdoor or indoor usage and require 115v AC power to operate the control panel. As with all of our equipment, field technicians are available to help install the units or to fully operate them for the duration of your project.



#### FEATURES

- Skid mounted units for easy mobility
- Achievable dew point from -40 to -100°F
- Outdoor rated electronic control panel
- High and low pressure available (70PSI– 350PSI)
- Large and small volume units available (250CFM – 5400CFM)



## FULL PRODUCT LINE

### Desiccant Dryers

Model	Capacity (SCFM)	Dimensions (in)	Weight (lbs)
RDH-260	260	90 x 42 x 47	1150
RDH-450	450	92 x 42 x 60	1800
RDH-800-S	800	83 x 60 x 80	3200
RDH-930-G	930	80 x 75 x 71	3800
RDH-1550-G	1550	79 x 83 x 78	5000
RDH-2100-G	2100	78 x 82 x 102	8000
RDH-3000-G	3000	81 x 91 x 115	9200
RDH-5400-G	5400	81 x 91 x 153	16000

### Desiccant Dryers *with Air Driven Fan Motor Aftercooler Mounted*

Model	Capacity (SCFM)	Dimensions (in)	Weight (lbs)
FR-250-AC	250	86 x 50 x 56	1150
RDH-260-GAC	260	86 x 56 x 50	1750
FR-400-AC	400	70 x 57 x 63	2000
RDH-450-GAC	450	82 x 50 x 69	2200
FR-800-AC	800	83 x 60 x 80	3200
RDH-930-GAC	930	87 x 75 x 73	3800
RDH-1550-GAC	1550	88 x 83 x 88	6000
RDH-2100-GAC	2100	78 x 82 x 101	6000

### High Pressure Desiccant Dryers

Model	Capacity (SCFM)	Dimensions (in)	Weight (lbs)
RDHHP-715	1200 @ 350 PSIG	96 x 78 x 96	4000
RDHHP-930	1600 @ 350 PSIG	79 x 78 x 83	4500
RDHHP-1550	2800 @ 350 PSIG	79 x 78 x 83	6150
RDHHP-930-500	1800 @ 500 PSIG	79 x 78 x 83	4500

### High Pressure Desiccant Dryer *with Air Driven Fan Motor Aftercooler Mounted*

Model	Capacity (SCFM)	Dimensions (in)	Weight (lbs)
RDHHP-1550-GAC	2800 @ 350 PSIG	88 x 78 x 83	7000

### Refrigerated Compressed Air Dryer

Model	Capacity (SCFM)	Dimensions (in)	Weight (lbs)
RD-1600	500 - 1600	72 X 52 X 60	1200

### High Pressure Aftercoolers *with Oil Removal Filters and Air Driven Motors*

Model	Capacity (SCFM)	Dimensions (in)	Weight (lbs)
AC 1200-350	1200 @ 350 PSIG	73 x 48 x 72	1200
AC 3000-350	3000 @ 350 PSIG	74 x 48 x 72	1800

### Aftercoolers/Seperators *with Air Driven Fan Motor Aftercooler Mounted*

Model	Capacity (SCFM)	Dimensions (in)	Weight (lbs)
AFC-1000	1000	46 x 28 x 60	600
AFC-1600	1600	73 x 48 x 72	1000
AFC-3000	3000	73 x 60 x 108	1200

### 660 Gallon Air Receiver Tank

Model	Capacity (SCFM)	Dimensions (in)	Weight (lbs)
T660	165 & 200 PSIG	60 x 48 x 130	1700

### Other Accessories

Model	Dimensions
Air Hose	2" x 50' & 3" x 50'
Step Deck Trailer	48" x 102"

*Our product line is specifically tailored to best fit our customers rental needs. We pride ourselves in being your dryer knowledge experts and are available across the nation 24/7.*

*For all your rental needs, contact your local Mustang Services customer representative!*

